TEKNOJET 1SN 250

EN 1829 - 2

Professional water jet cleaners



Features: R S.F. 4:1

Alternative Versions: F Forever

Code	Hose Size			Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight	
	D.N.	mm	Inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/mt	lb/ft
TJ1SN04	6	6.4	1/4"	13.1	0.52	250	3625	1000	14500	100	3.94	0.21	0.14
TJ1SN05	8	7.9	5/16"	14.7	0.58	250	3625	1000	14500	115	4.53	0.25	0.17
TJ1SN06	10	9.5	3/8"	17.2	0.68	250	3625	1000	14500	130	5.12	0.34	0.23
TJ1SN08	12	12.8	1/2"	19.6	0.77	250	3625	1000	14500	180	7.09	0.48	0.32

Available colors: BLACK - BLUE - RED - GREY

To order different colors, add B (Blue), R (Red), or G (Grey) at the end of the code.

To order the Forever version, add FV at the end of the code.

Hose layline example



OPERATING TEMPERATURE RANGE:
-40°C/+135°C
(-40°F/+275°F)
with peaks of +150°C (302°F)

TUBE:
Hot water, detergent and oil synthetic rubber

REINFORCEMENT:
1 high tensile steel braid

COVER:
Standard cover: Synthetic rubber (MSHA approved)
Forever FV: Polyethylene-coated synthetic rubber with extreme resistance to abrasion, ozone, and UV (MSHA approved)

CERTIFICATIONS:

U.S. Department of Labor MSHA Mine Safety & Health Administration